

THE RIGHT VENTILATION FOR YOUR ENCLOSURE

SOLIFLEX - Filter fans & exhaust filters

SOLIFLEX filter fans and outlet filters effectively ventilate enclosures and control panels if the ambient temperature is lower than the internal enclosure temperature. Combined with thermostats, additional energy can be saved. The fan only operates when it is actually needed.

Our SOLIFLEX filter fans are also available in a reversed (blowing in) air flow mode and with NEMA 3R / IP 55 protection class.



Filter fans

For a constant enclosure climate

- ✓ Wall or roof mounted
- ✓ Tool free installation and filter change
- ✓ Standard enclosure cutouts (5 sizes)
- ✓ Matching exhaust filters available
- ✓ Protection hoods against water jets and dust



Model	Air flow unimpeded	Available voltages	Dimensions (H x W x D) mm	Mounting
FL 4010 A	12 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz	106.5 x 106.5 x 66.6	Wall mounted
FL 4023 A	21 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz	106.5 x 106.5 x 79.5	Wall mounted
FL 4210 A	67 m³/h	120 V ~ 60 Hz, 230 ~ 50/60 Hz	150 x 150 x 73 mm	Wall mounted
FL 4210 D	47 m³/h	24 V DC, 48 V DC	150 x 150 x 73 mm	Wall mounted
FL 4411 A	110 m³/h	120 V ~ 60 Hz, 230 ~ 50/60 Hz	204 x 204 x 95,5	Wall mounted
FL 4610 D	225 m³/h	24 V DC, 48 V DC	250 x 250 x 124.2	Wall mounted
FL 4620 A	230 m³/h	120 V ~ 60 Hz, 230 ~ 50/60 Hz	250 x 250 x 124.2	Wall mounted
FL 4621 A	105 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz	250 x 250 x 111.8	Wall mounted
FL 4830 A	455 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz 380-415 V 50 Hz 3~ 400-460 V 60 Hz 3 ~	325 x 325 x 160.2	Wall mounted
FL 4883 A	820 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz 400/460 V ~ 50/60 Hz 3~	325 x 325 x 158.5	Wall mounted
FL 6064 A	275 m³/h	120 V ~ 60 Hz, 230 ~ 50/60 Hz	147 x 457 x 457	Roof mounted
FL 6065 A	490 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz 400/460 V ~ 50/60 Hz 3~	147 x 457 x 457	Roof mounted
FL 6085 A	630 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz 400/460 V ~ 50/60 Hz 3~	147 x 457 x 457	Roof mounted
FL 6095 A	970 m³/h	120 V ~ 60 Hz, 230 V ~ 50/60 Hz 400/460 V ~ 50/60 Hz 3~	147 x 457 x 457	Roof mounted
FL 6995 A	1,400 m³/h	120 V ~ 60 Hz, 230 ~ 50/60 Hz 400/460 V ~ 50/60 Hz 3~	147 x 457 x 457	Roof mounted
FL 6996 A	1,500 m³/h	230 V ~ 50/60 Hz	241 x 550 x 550	Roof mounted